

**NDT INTERNATIONAL, INC.**

711 S. CREEK ROAD  
WEST CHESTER, PA 19382

Tel: 610.793.1700 Fax: 610.793.1702  
E-mail: info@ndtint.com

## ULTRASONIC TRANSDUCERS AND ACCESSORIES



■ **STANDARD CONTACT (Single Element)**

1 to 10 MHz, .18" to 1.125" Diameter  
Prefix "C" for BNC Connector, "CF" for Microdot Connector,  
or "PF" for Protective Face

■ **DUAL ELEMENT (Integral Cable) Type "DFP" and "DHT"**

1 to 10 MHz, .25" to .5" Diameter, BNC or LEMO connectors  
Available in High Temperature version (to +500°F. Max.)

■ **DUAL ELEMENT (No Cable) Type "DFR" and "DR-DHT"**

1 to 10 MHz, .375" and .5" Diameter, Microdot connectors  
Available in High Temperature version (to +500°F. Max.)

■ **REPLACEABLE DELAY LINE (Single Element) Type "GD", "GRD" or "MRD"**

2.25 to 25 MHz, .125" to .500" Diameter, Microdot Connector  
Standard, Spring-Case and Miniature

■ **STANDARD ANGLE BEAM Type "ABS"**

1 to 10 MHz, and AWS D1.1  
.5" to 1.0" Diameter, .5" x .5", .5" x 1.0", and .75" x .75" Element  
BNC Connector, 2 screw attachment

■ **FINGERTIP REMOVABLE ANGLE BEAM Type "ABFR"**

2.25 to 10 MHz, .25" to .500" Diameter  
Microdot Connector, 2 screw attachment

■ **FINGERTIP QUICKCHANGE ANGLE BEAM Type "ABFQ"**

2.25 to 10 MHz, .125" to .500" Diameter  
Microdot Connector, Threaded Housing

■ **FINGERTIP POTTED (Integral Shoe) ANGLE BEAM Type "ABFP"**

2.25 to 10 MHz, .18" x .18" or .25" x .25" Element  
45°, 60°, 70° and 90° Effective Angle

■ **REMOVABLE ANGLE BEAM SHOES (Wedges)**

45°, 60°, 70° and 90° Effective Angles  
for ABS, AFR and ABFQ Transducers

■ **IMMERSION TRANSDUCERS Type "ISL", "IRA", "ILD", "IF", "IPM", "IPU" & "IP"**

1 to 25 MHz, .25" to 1.0" Diameter, UHF Connector  
Pencil, Reflector, Slimline, Large Diameter and Flanged Housings  
S.S. Serach Tubes: 2", 4", 6", 12", 18" and 24" Lengths  
Reflectors and Adaptors

■ **TRANSDUCER CABLES**

BNC, Microdot, LEMO or UHF as Standards; Single, Dual or special coaxial cables

Call for anything you don't see listed above.