

ULTRASoniX™

High Performance Ultrasonic Couplant

UltraSoniX is a high performance ultrasonic couplant for flaw inspection and thickness gaging that is compatible with most materials, with good multi-metal corrosion inhibition and is formaldehyde and glycol ether free.

PRODUCT DESCRIPTION

High viscosity couplant remains in place on vertical and overhead surfaces.

5°F to 220°F (-15°C – 104.4°C) temperature range for most flaw detection and thickness gaging applications.

Better multi-metal corrosion inhibition than most UT couplants.

Slow drying for extended inspection time.

Reduced surface tension provides fast wetting.

Contains no glycerin which can interfere with subsequent penetrant inspection.

Water soluble: easier to remove than most ultrasonic couplants by wet or dry wiping or water wash.

Environment and operator friendly – no formaldehydes, nitrates, nitrites or glycol ethers.

Lower residue than most UT couplants.

Safety: No formaldehyde, nitrates, nitrites or glycol ethers

Packaging: carton of (12) 4-oz/118 ml bottles
carton of (12) 8-oz/236.6 ml bottles
carton of (12) 8-oz/236.6 ml oval bottles
carton of (12) 12-oz/340 ml bottles

1-gallon/3.8 liter cubitainer
5-gallon/19 liter cubitainer
55-gallon/208 liter drum

PRODUCT SPECIFICATIONS

Viscosity: ~85,000 cps, Brookfield helipath E @ 1.5 RPM

~40,000 cps, LVT 4 @ 6 rpm

pH: 8.0 nominal at 20°C

Operating Temperature: 5°F to 220°F (-15°C – 104.4°C)

Halogens and Sulfur: less than 50 ppm

ASTM F519, conforms: ASTM F519 describes mechanical test methods and defines acceptance criteria for exposure to chemicals encountered in Service Environments, such as fluids, cleaning treatments or maintenance chemicals including ultrasonic couplants that come in contact with the plated/coated or bare surface of the steel.

This test method provides a means by which to detect possible hydrogen embrittlement of steel parts (plated/coated or bare) due to contact with chemicals during manufacturing, overhaul and service life.



Removal: Wipe with wet or dry paper or cloth rag or water wash.

NDT INTERNATIONAL INC.
711 S. Creek Road,
West Chester PA U.S.A.
19382-8013



Tel: (610) 793-1700
Fax: (610) 793-1702
Info@ndtint.com
www.ndtint.com